


FOUR FINGER CLIPS



PART NUMBER	OUTSIDE DIAMETER	OVERALL LENGTH	OPERATING RANGE PIN DIA.	TEST PIN DIAMETER	MAXIMUM INSERTION FORCE	MINIMUM WITHDRAWAL FORCE
D-1S	0.044	0.065	.015 - .022	0.018	135 GM	25 GM
D-1SH	0.044	0.065	.015 - .022	0.018	260 GM	55 GM
D-3S	0.044	0.065	.015 - .022	0.018	520 GM	120 GM
D-1L	0.044	0.083	.015 - .022	0.018	45 GM	15 GM
D-3	0.044	0.083	.015 - .025	0.017	270 GM	90 GM
D-3H	0.044	0.083	.015 - .025	0.018	675 GM	200 GM
D-4	0.053	0.117	.022 - .032	I - 0.026 W - 0.024	385 GM	50 GM
D-5	0.069	0.150	.036 - .050	0.040 0.030	325 GM 55 GM	60 GM 15 GM
D-6	0.080	0.150	.040 - .059	I - 0.050 W - 0.040	375 GM	35 GM
D-7S	0.064	0.095	.032 - .045	0.040	5 LB	200 GM
D-7	0.0635	0.120	.032 - .046	0.041 0.039	350 GM	55 GM
D-7L	0.064	0.120	.032 - .045	I - 0.040 W - 0.035	2.25 LB	110 GM
D-8	0.088	0.124	.048 - .064	I - 0.060 W - 0.050	440 GM	60 GM
D-9	0.108	0.148	.065 - .082	I - 0.074 W - 0.072	3 LB	230 GM

NOTE: ALL CLIPS PRODUCED FROM BeCu ALLOY 172 1/2 HD AND HEAT TREATED AFTER FORMING.
ALL SPECIFICATIONS REFER TO CLIPS THAT ARE NOT PLATED.

THE ABOVE INFORMATION IS PROVIDED FOR REFERENCE ONLY. ENGINEERING DRAWINGS CAN BE PROVIDED.

ditron^{inc.}

81 SOUTH GREENHAVEN ROAD, PO BOX 375, STORMVILLE, NEW YORK 12582
TELEPHONE: (845) 227-9300
FAX: (845) 227-2872
WWW.DITRONINC.COM